

FIG 1




FIG. 2






FIG. 3



(a)




(b)

BEST AVAILABLE COPY

FIG. 4




(a)




(b)

BEST AVAILABLE COPY

FIG. 5



(a)



(b)

BEST AVAILABLE COPY

FIG. 6


(A) MATERIAL 1

ASPECT RATIO = 506 %




(B) MATERIAL 2

ASPECT RATIO = 347 %



(C) MATERIAL 3

ASPECT RATIO = 300 %



BEST AVAILABLE COPY

FIG. 7




FIG. 8




FIG. 9




FIG. 10

Inventor: Ando, et al
Docket No.: 12052.33USD1
Title: BILLET FOR COLD FORGING, METHOD OF MANUFACTURING BILLET FOR COLD FORGING, METHOD OF CONTINUOUSLY COLD-FORGING BILLET. METHOD OF COLD-FORGING
Attorney Name: Curtis B. Hamre
Phone No.: (612) 336-4722
Sheet 10 of 42




FIG. 11







FIG. 12



MARTENSITIC MATERIAL
(a) PRIOR TO SPHERODIZING ANNEALING
× 2.1




BEST AVAILABLE COPY

FIG. 13



PRIOR TO SPHERODIZING ANNEALING
SURFACE LAYER $\times 100$

FIG. 14



PRIOR TO SPHERODIZING ANNEALING
SURFACE LAYER AND INTERMEDIATE LAYER $\times 200$


BEST AVAILABLE COPY

FIG. 15



PRIOR TO SPHERODIZING ANNEALING
1/2 R PART $\times 400$

FIG. 16




PRIOR TO SPHERODIZING ANNEALING
CENTRAL PART $\times 400$

FIG. 17



MARTENSITIC MATERIAL
AFTER SPHERODIZING ANNEALING PATTERN 1
x 2. 1


(a)



(b)


BEST AVAILABLE COPY

FIG. 18



AFTER SPHERODIZING ANNEALING PATTERN 1
SURFACE LAYER $\times 100$

FIG. 19



AFTER SPHERODIZING ANNEALING PATTERN 1
SURFACE LAYER $\times 400$

BEST AVAILABLE COPY


FIG. 20



AFTER SPHERODIZING ANNEALING PATTERN 1
1/2 R PART \times 400


BEST AVAILABLE COPY

FIG. 21



MARTENSITIC MATERIAL
AFTER SPHERODIZING ANNEALING PATTERN 2
x 2. 1

(a)




(b)

FIG. 22



AFTER SPHERODIZING ANNEALING PATTERN 2
SURFACE LAYER $\times 100$

FIG. 23



AFTER SPHERODIZING ANNEALING PATTERN 2
SURFACE LAYER $\times 400$

BEST AVAILABLE COPY

FIG. 24



AFTER SPHERODIZING ANNEALING PATTERN 2
1/2 R PART \times 400

BEST AVAILABLE COPY

FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29







FIG. 30



(a)




(b)




(c)

FIG. 31




(a)




(b)

FIG. 32




(a)




(b)

FIG. 33




(a)



(b)


FIG. 34

(INVENTIVE COLD-FORGING METHOD)



(a)

(CONVENTIONAL COLD-FORGING METHOD)



(b)

FIG. 35






FIG. 36




(a)

FOUR ARBITRARY SPOTS




(b)



(c)


FIG. 37

SLIP TORQUE




(a)

S - N CURVE (ROTATIONAL BENDING FATIGUE TEST)




(b)

S - N CURVE (SOLID BENDING FATIGUE TEST)



(c)

FIG. 38



BEST AVAILABLE COPY

FIG. 39




FIG. 41



FIG. 43




FIG. 44




FIG. 45




FIG. 46





FIG. 47






FIG. 49

	Billet manufacturing process					Aspect ratio of carbide (%)	Crack percentage % N=100
	Spherodizing annealing prior to drawing	Drawing	Cutting	Spherodizing annealing subsequent to drawing	Shot bonderizing		
Material 1	None	None	○	○	○	506	35%
Material 2	None	(20%) ○	○	○	○	347	5%
Material 3	○	(20%) ○	○	○	○	300	0%

$$\text{Aspect ratio (\%)} = b/a \times 100$$

